COUNTRY 210 PERFORMER SERIES

COUNTRY STOVES 210 PERFORMER T-TOP AND STEP-TOP FREESTANDING WOOD STOVES



210 Performer simple. Stainless steel burn tubes and state-of-the-art secondary burn technology provide the

long, clean burns Country is famous for.

Step-Top 210 shown with 24K gold

24K gold plated cast legs. (Step-Top 210 available with arched door only)

plated arched door and Olympic

We recently redesigned the 210, giving you two new looks to choose from. Try the more contemporary Step-Top with it's arched door or the classic T-Top with a traditional door. Either is available with gold, black, or nickel door and accents. Whichever model you choose, the EPA Phase II certified, non-catalytic 210 Performer will provide you and your home with a lifetime of warmth.



- All secondary burn components inside the firebox made of stainless steel for long service life
- Singular draft control technology offers ease of operation
- Mobile home approved for freestanding applications, pedestal or leg mounted
- See back of flyer for a wide variety of options allowing you to add distinction and a personal touch to your handcrafted Country Stove
- · Choose from T-Top or Step-Top styles
- · Multi-level top provides increased surface area for greater heat transfer and dual cook-top surfaces



Options and Specifications for the 210 Performer Series Wood Stoves

THESE SPECIFICATIONS ARE FOR REFERENCE ONLY. DO NOT USE FOR INSTALLATION.

OUR COMMITMENT

For the last 25 years, we have prided ourselves on creating the finest, hand-crafted stoves available. We've grown and changed over the years, but we haven't lost what made us successful to begin with - a commitment to providing you and vour family a lifetime of warmth.

LIMITED LIFETIME WARRANTY

We are proud to stand behind our stoves. We prove it by offering a true Limited Lifetime Warranty on all of our products. See your Country Stove professional for more details.

SPECIFICATIONS

SS210 & ST210

HEATING CAPACITY

1,200 - 2,000 sq. ft. MAX. HEAT OUTPUT

76,000 BTU's/hr

MAX. BURN TIME

7-9 Hours COMBUSTION SYSTEM

Non-Catalytic

STOVE PIPE DIAMETER

LOG LENGTH

20" Max / 18" Rec

PA GRAMS PER/HR

FIREBOX

20" width x 18" depth

OREGON DEQ EFFICIENCY

COUNTRY SIGNATURE STOVES

These are not assembly line produced heaters, but premium hand-crafted appliances. Each stove is constructed almost entirely by a single craftsman, giving the builder a special pride and responsibility

in workmanship assuring you a lifetime of warmth



- * Heating capacity varies due to home insulation, floor plan and climate.
- * Burn times will vary depending on species of wood, pipe configurations, and burn habits.
- ** Efficiency varies slightly with various pipe configurations.

This appliance must be installed in accordance with local building codes.

PERFORMER SERIES FREESTANDING WOOD STOVE:

- ▲ Fasy to install with close clearances
- ▲ Large 2.1 cubic foot firebox for easy loading
- ▲ All secondary burn components inside the firebox made of stainless steel for long service life
- ▲ Singular draft control technology offers ease of operation
- ▲ Mobile home approved for freestanding applications, pedestal or leg mounted
- ▲ See below for a wide variety of options allowing you to add distinction and a personal touch to your handcrafted Country Stove






Shown with metallic black painted traditional pedesta


T-TOP WITH LEGS

T-TOP WITH PEDESTAL


NOTICE: These specifications are used for reference only and shall not be used for actual installation. Use installation instructions for actual installation

SIDE WALL/BACK WALL





CORNER



210 PERFORMER SERIES DIMENSIONS AND CLEARANCES

	Α	В	С	D	E	F	G	Н	- 1	J	K	L	T	X	Υ	Z
Single Wall Connector	16"	14"	24"	14-1/2"	6"	9"	18"	44"	52"	35"	16"	8"	63"	N/A	N/A	N/A
Single Wall with Shield Connector	10"	8"	24"	14-1/2"	6"	9"	18"	44"	46"	35"	16"	8"	63"	N/A	N/A	N/A
Double Wall Connector	10"	8"	18"	8-1/2"	6"	6"	15"	44"	46"	35"	16"	8"	59"	48"	48"	72"

Weight: 380 lbs. (SS210), 390 lbs. (ST210)

Stove Depth: 213/4" (door opening to rear shield)

Stove Height: With pedestal: 34 1/2" (SS210) 34 1/4" (ST210) With legs: 31" (SS210) 303/4" (ST210)

- A= Flue Collar to Back Wall B= Stove to Back Wall
- C= Flue Collar to Side Wall D= Stove to Side Wall
- F= Stove Corner to Wall G= Flue Collar to Wall
- K= Front of Stove
- L= Measured from Door Opening E= Back of Stove Heat Shield
- H= Pad Depth Minimum
- J= Pad Width Minimum
- I= Pad Depth to Back Wall (B-E+H) T= Pad Depth to Corner
- X= Minimum Alcove Width
- Y= Maximum Alcove Depth
- Z= Minimum Alcove Height

DOOR & GLASS OPTIONS

SS210 T-Top available only with traditional door. ST210 Step-Top available only with arched door. All etched glass options are available for all stoves



Hand finished 24k gold plated traditional door with Evergreen etched glass



Arched door in metallic black with Sails etched glass



Hand finished 24k gold plated arched door with Floral etched glass.



traditional door with Cattails

LEG OPTIONS

Choose from four options:



- Cascade steel leg
- Olympic cast black leg Olympic cast leg in hand
- finished 24 karat gold plating D. Olympic cast leg in hand finished nickel plating



STOVE BLOWER

Country's optional variable speed, 700 cubic feet per minute (CFM) blower is the largest blower available for any stove. It is custom-designed and moves a high flow of air volume while remaining whisper guiet at higher settings. The FSB700 fits any of the Country's freestanding stoves while utilizing the high heat and natural convection from the stove body

YOUR AUTHORIZED COUNTRY STOVES DEALER



COUNTRY STOVES, INC. D. Box 959, Auburn, WA 98071-0959

www.countrystoves.com

© 2002 Country Stoves, Inc.





S/W Design #105530 11/2002 30M